

- a tube hopper for receiving a supply of empty cigarette tubes,
- a discharge device for a tube, which is to be filled with a tobacco material,
- a holder <u>mechanism within said conveyor</u> [means for holding said tube during the filling operation], and
- a cigarette hopper for receiving [the] filled cigarettes, said discharge device being a lifting device which raises a tube from below out of said tube hopper, wherein, said lifting device comprises a pusher, the top edge of which has a longitudinal recess.
- 2. The tube or cigarette conveyor as set forth in claim 1, wherein said pusher in said tube hopper is arranged so that said longitudinal recess, in the lowered condition, forms part of the bottom at the lowest point of said tube hopper.
- 3. (Once Amended) The tube or cigarette conveyor as set forth in claim 1 [or 2], wherein said pusher is arranged at a straight wall of said tube hopper, along which it is raised, deflectors being arranged at the upper part of said wall, which are capable of returning all raised tubes back into said tube hopper, except for the one located in said recess of said pusher.
- 4. The tube or cigarette conveyor as set forth in claim 3, wherein said deflectors comprise at least one, but preferably two, pivot clips oriented transversely to said

longitudinal recess of said pusher and initially coming to rest on said raised tube upon raising of said pusher, while, upon a further raising, they slide past said tube into slots in said pusher so that they are located underneath said tube and transport said filled cigarette into said cigarette hopper upon lowering of said pusher.

- 5. The tube or cigarette conveyor as set forth in claim 4, wherein said clips are arranged on a common pivoting axis and are pre-tensioned by means of a lever weight in the direction of rotation so that, upon raising of said tube, their middle sections initially lightly press on said tube, while their front sections deflect further tubes.
- 6. (Once Amended) The tube or cigarette conveyor as set forth in [any of the claims 1 to 5] claim 1, wherein said [means for holding said tube during said filling procedure] holder mechanism/comprises a recessed [surround] forming member which surrounds [the] said tube or cigarette from above at least in part.
- 7. (Once Amended) The tube or cigarette conveyor as set forth in claim 6, wherein said longitudinal recess of said pusher, in the raised condition, together with said recessed [surround] forming member of said holder [means] mechanism, substantially [completely] surrounds said tube during said filling procedure.
- 8. (Once Amended) The tube or cigarette as set forth in claim 6 [or 7], wherein said holder [means] mechanism further comprises sensors, in particular a photocell, which detects the presence of a tube or cigarette or the empty condition

of said holder [means] mechanism.

9. (Once Amended) The tube or cigarette conveyor as set forth in [any of the claims 1 to 8] claim 1, wherein said tube hopper and/or said cigarette hopper are configured as drawers, in particular at least the bottom of which is configured latticed, and preferably a removable catchment vessel for the tobacco material is provided below said tube hopper and/or said cigarette hopper.

10. (Once Amended) A tobacco rod shaping [means] mechanism, in particular for a do-it-yourself cigarette maker, comprising:

- a funnel-shaped tobacco material infeed section,
- a singling device for sald tobacco material, and
 - a tobacco rod compression [means] mechanism, said singling [means] device being a roller, partly surrounded by a housing, with a plucking [means] mechanism arranged at the circumference of said roller, in particular a plucking roller with plucking pins, by means of which said tobacco material is conveyed into said tobacco rod compression [means] mechanism, wherein a wall section is pivot-mounted [so that it can be pivoted out of the way of said roller from a secured working position in order to remove excess tobacco downwards, where it can preferably drop into a removable catchment means].

11. (Once Amended) The tobacco rod shaping mechanism [means] as set forth in claim 10, wherein said funnel-shaped infeed surface comprises at least one wall

section oriented radially to said roller axis.

12. (Once Amended) The tobacco rod shaping mechanism [means] as set forth in claim 10 [or 11], wherein said tobacco rod compression [means] mechanism comprises a tobacco chamber, which can be opened up and closed by at least one side, the travelling side part of said chamber preferably being shifted by means of a cam from the opened position into the closed position, in overcoming a spring preload, and the opening width of the chamber is preferably settable by means of a positioner.

13. (Once Amended) The tobacco rod shaping [means] mechanism as set forth in [any of the claims 10 to 12] claim 10, wherein said wall sections, surrounding said tobacco rod to be shaped, are provided with an anti-stick coating.

14. (Once Amended) The tobacco rod shaping [means] mechanism as set forth in [any of the claims 10 to 13] claim 10, wherein said roller is [inserted] insertably removable.

15. (Once Amended) The tobacco rod shaping [means] mechanism as set forth in [any of the claims 10 to 14] claim 10, wherein said plucking roller is made of a material resistant to corrosion, for example aluminum, preferably with an A1O₂ surface finish.

- 16. A tobacco rod conveyor for a do-it-yourself cigarette maker comprising a tappet, for shuttling in and out of a chamber containing a tobacco plug, wherein said tappet comprises an outer tube, in which a guide rod runs, said guide rod comprising at its front end an insertion aid for said tobacco rod.
- 17. The tobacco rod conveyor as set forth in claim 16, wherein said guide rod comprises at its rear end an appendage, by which it can be withdrawn in overcoming the pressure of a spring provided in said outer tube, said insertion aid for said tobacco material thereby entering said outer tube.
- 18. (Once Amended) The tobacco rod conveyor as set forth in claim 16 [or 17], wherein said insertion aid has substantially the length of said tobacco rod and is shaped so as to assist pushing of said tobacco rod only in the conveying direction, and is configured [, for example,] as a toothed blade, a shingled scoop or spiral guide.
- 19. (Once Amended) The tobacco rod conveyor as set forth in claim 16 [to 18], wherein said tappet is shifted back and forth at its rear end by means of an eccentric drive, preferably a support engaging with said eccentric drive, in particular a retaining lever, holds said outer tube in position upon removal of said guide rod after conveyance of said tobacco rod.
- 20. A tube aligning device, especially as provided for a do-it-yourself cigarette maker, comprising a receiving element for said tube consisting of a circular gap

between a housing and a mandrel secured in said housing, wherein said circular gap comprises substantially the axial length of a digarette tube and at the insertion end a device is provided with which said circular gap can be constricted.

21. (Once Amended) The tube aligning device as set forth in claim <u>20</u>, wherein said constricting device comprises a clamping screw [,] for screwing to said insertion end [,] as well as collets [,] arranged between mandrel and housing, said gap between said collets and said mandrel being constricted by turning said clamping screw.

22. (Once Amended) The tube aligning device as set forth in claim [19 or 20] <u>21</u>, wherein, in the region of said collets, an O-ring may be provided around said mandrel, at which preferably an adapter ring is arranged for fixing and centering.

23. (Once Amended) A do-it-yourself cigarette maker comprising: [one or more of the following component assemblies:]

- a tube or cigarette conveyor [as set forth in claims 1 to 9];
- a tobacco rod shaping means [as set forth in claims 10 to 15];
- a tobacco rod conveyor [as set forth in claims 16 to 19];
- a tube aligning device [as set forth in claims 20 to 22].

24. (Once Amended) The do it-yourself cigarette maker as set forth in claim 23 [or 24, wherein said] having a tappet [of] in said tobacco rod conveyor, [said] a tobacco compression chamber [of] in said tobacco rod shaping means, and [said] a